



EMRA Tech Checklist

Note: Fairing lowers must be removed Prior to Technical Inspection. NO Exceptions

Fluids Note: The use of antifreeze is strictly prohibited

- ☐ All drain plugs and filler caps (except fuel cap) safety wired
- ☐ Oil filter bolt safety wired, oil filter cans safety wired or clamped and wired
- ☐ Vent and overflow tubes routed into catch can
- ☐ Brake (and clutch if applicable) master cylinder taped or wrapped with terry cloth

Brakes

- ☐ Banjo bolts safety wired or siliconed
- ☐ Caliper mounting bolts and/or nuts safety wired
- ☐ Test lever travel front and rear
- ☐ Front brake lever bolt safety wired or siliconed or secure with castellated nut and cotter pin
- ☐ Front brake lever guard

Front forks

- ☐ Axle nut secured with safety wire or cotter pin
- ☐ Axle pinch bolts secure with safety wire, nuts safety wired or self locking and siliconed
- ☐ Appropriate engine protection with race specific case covers and/or frame savers

Electrical

- ☐ Functioning kill switch

Swingarm

- ☐ Axle nut secured with safety wire or cotter pin. Reusable cotter pins must be safety wired
- ☐ Rear sprocket guard (Shark guard) - no access for limbs between swingarm, lower chain and rear sprocket

Wheels/Tires

- ☐ No loose or broken spokes on wire spoke wheels
- ☐ Acceptable tread depth where applicable (not less than wear bars)
- ☐ Metal valve stem caps

Bodywork/Exhaust

- ☐ All bodywork and exhaust headers and pipes must be securely fastened to the bike
- ☐ Lower fairing is sealed and free of holes/cracks
- ☐ No sharp or broken edges that could result in injury
- ☐ Regulation size and colour for race numbers (legibility is key)
- ☐ All stands removed. Kick start levers either removed or secured with safety wire or cable tie

Drive chain

- ☐ Clip style master links **must be** safety wired and oriented in the proper direction

Rider equipment

- ☐ Helmet Snell M2010 or M2015, ECE 22.05 P, BSI 6658 Type A, JIS 8133:2007 all qualify if in good condition, unaltered, and within 5 years to the month manufacture date. GoPro/Camera mounts are disallowed
- ☐ Leathers one or two piece (must zip together at waist) in serviceable condition, no holes or tears
- ☐ Separate race style back protector or suitable protector built into suit, thin foam pads are not acceptable
- ☐ Serviceable boots (at least 8" high) and gauntlet style gloves, no holes or tears
- ☐ Medical Data Carrier on lower right side of helmet

BIKE # : _____ **Red** _____ **Black** _____ **Tech Completed by:** _____